

AURA-8000

www.posiflex.com

POSIFLEX
Your Success is Our Vision



Key Features

- ▶ 3" advanced high-speed thermal printer with auto cutter
- ▶ Detailed curvy surface in a delicate design
- ▶ Printing speed up to 220 mm per second, 80 (or 58) mm paper width / 64 (or 53) mm print width
- ▶ High-resolution print up to 8 dots / mm and 512 dots / line (Max. 576 dots / line)
- ▶ QR code and PDF417 printing support
- ▶ Low noise thermal printing
- ▶ Drop-and-load structure for paper roll loading
- ▶ Cash drawer control up to 2 cash drawers
- ▶ Enhanced capability in kitchen bell for reminder function
- ▶ External cover for further spill-resistant and dust-proof functions (Optional)
- ▶ Desktop or wall mount solution



Spill-resistant and dust-proof cover

AURA-8000

Spill-Resistant Speedy Thermal Printer



The AURA-8000 is a rugged and high performance printer up to 220 mm per second. Its optional spill- and dust-resistant top cover is thoughtful design for retailers to extend their business in much more environments. Speedy printing makes the AURA-8000 do a good role as a payment receipt printer and an information printer for kitchen use. Additionally, the AURA-8000 features easy paper replacement and wall-mounted function.

The AURA-8000 showcases high reliability and performance for harsh and busy applications.

Specification	AURA-8000
Print Speed	220 mm / sec (Max.)
Print Resolution	8 dots / mm, default 512, 576 (Max.) dots / line
Paper Width	83 (Or 58) + 0 / -1 mm
Printing Width	64 mm (For 512 dots / line) / 72 mm (For 576 dots / line)
Input Buffer	10 KB
LED indicator	Power : Green, Error : Red, Paper Out : Red
Cutter	Auto and additional manual cutters
Power Voltage	24V
Power Consumption	60W
Paper Spacing Plate	For 80 or 58 mm paper width
Interface	serial, parallel, USB or LAN port
Dimension (W x D x H in mm)	148 x 205 x 143
Weight (N. w. in kg)	1.2
Color	Ivory white or black
Operating Condition	5 °C to 40 °C (20% ~ 85%RH, no condensation)
Language Support	
International Character Set	15 international character sets supported (Denmark I, Denmark II, Ex-Yugoslavia, France, Germany, Italy, Japan, Korea, Latin America, Norway, Spain, Spain II, Sweden, UK, USA)
Character Code Page	23 code pages supported (Power on default code page can be set infactory by software program)
Bar Code Printing	UPC-A/E, EAN13/8, ITF, CODE39/93/128, CODABAR, QR Code, PDF417
Options	
Kitchen Bell	Alarm type KL-100 or buzzer type KZ-200
Wall Mount Kit	Yes
Spill Resistant & Dust Proof Cover	Yes
Certifications	

Design and Manufacturing In Taiwan by Posiflex Technology Inc.

2011 AURA80Q4C1

** The product information and specifications are subject to change without prior notice.

POSIFLEX Posiflex Technology, Inc.
Headquarters
No.6, Wuquan Rd., Wugu Dist., New Taipei City
248, Taiwan (R.O.C.)
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com